



Courtesy of Beddelleem NV

# Air Extremelight

Ultra-light chipboard for interior door cores

Air Extremelight is extremely light chipboard with a fine, sanded surface and a different density to the Air 400. This chipboard is perfectly suited for non-load bearing use in dry environments. It is suitable for applications in service class 1 (limited temperature and atmospheric humidity) and exclusively in biological hazard class 1 of EN Standard 335-3.

## Applications

- Doors

## Characteristics



Lightweight



# Air Extremelight

## Applications

Tests by Warrington Fire (Belgium) and Effectis (France) have demonstrated that the Air Extremelight is particularly suitable for use as a core for interior doors with a fire resistance of 30 to 60 minutes. The light weight of the carrier board demands less of the hinges than other, heavier board material. The result is a door that is sturdy but light, with minimal distortion in a fire. The ultra-light Air Extremelight boards are also suitable for building stands.

## Technical specifications

General characteristics + Standard	Unit	Average values		
Thickness EN 324-1	mm	32	33	33,5
Density EN 323	kg/m <sup>3</sup>	430 +/-5%	430 +/-5%	430 +/-5%
Moisture level EN 322	%	5-10	5-10	5-10
Technical characteristics + Standard	Unit	5/95 percentile values		
Bending strength EN 310	N/mm <sup>2</sup>	2,5	2,0	2,0
Internal bond EN 319	N/mm <sup>2</sup>	0,17	0,14	0,14
Bending stiffness EN 310	N/mm <sup>2</sup>	450	400	400

Air Extremelight comes under formaldehyde emission class E1 and meets the general requirements described in Table 1 of standard EN312. The thickness tolerance (of the sanded board) deviates from this standard and is defined more strictly at +/-0.2 mm.

## Available dimensions and thicknesses

Air Extremelight is available on demand and can be made to order.

For our technical capabilities on custom thicknesses and dimensions, as well as minimum order requirements, please contact our sales team or email [info.panels@unilin.com](mailto:info.panels@unilin.com).

## Certificates

UNILIN Division Panels is actively committed to sustainable forest management. Air Extremelight is available on demand with PEFC and FSC® labelling.